



# Disk Scheduling



- The operating system is responsible for using hardware efficiently — for the disk drives, this means having a fast access time and disk bandwidth
- Minimize seek time
- Seek time  $\approx$  seek distance
- Disk **bandwidth** is the total number of bytes transferred, divided by the total time between the first request for service and the completion of the last transfer



# Disk Scheduling (Cont.)



- There are many sources of disk I/O request
  - OS
  - System processes
  - Users processes
- I/O request includes input or output mode, disk address, memory address, number of sectors to transfer
- OS maintains queue of requests, per disk or device
- Idle disk can immediately work on I/O request, busy disk means work must queue
  - Optimization algorithms only make sense when a queue exists



# Disk Scheduling (Cont.)



- Note that drive controllers have small buffers and can manage a queue of I/O requests (of varying "depth")
- Several algorithms exist to schedule the servicing of disk I/O requests
- The analysis is true for one or many platters
- We illustrate scheduling algorithms with a request queue (0-199)

98, 183, 37, 122, 14, 124, 65, 67


Head pointer 53



# FCFS



Illustration shows total head movement of **640 cylinders**






# SSTF



- Shortest Seek Time First selects the request with the minimum seek time from the current head position
- SSTF scheduling is a form of SJF scheduling; may cause starvation of some requests
- Illustration shows total head movement of **236 cylinders**





# SCAN




- The disk arm starts at one end of the disk, and moves toward the other end, servicing requests until it gets to the other end of the disk, where the head movement is reversed and servicing continues.
- **SCAN algorithm** Sometimes called the **elevator algorithm**
- Illustration shows total head movement of **208 cylinders**
- But note that if requests are uniformly dense, largest density at other end of disk and those wait the longest



# SCAN (Cont.)

queue = 98, 183, 37, 122, 14, 124, 65, 67

head starts at 53





# C-SCAN



- Provides a more uniform wait time than SCAN
- The head moves from one end of the disk to the other, servicing requests as it goes
  - When it reaches the other end, however, it immediately returns to the beginning of the disk, without servicing any requests on the return trip
- Treats the cylinders as a circular list that wraps around from the last cylinder to the first one
- Total number of cylinders?






# C-SCAN (Cont.)



queue = 98, 183, 37, 122, 14, 124, 65, 67  
head starts at 53





# C-LOOK




- LOOK a version of SCAN, C-LOOK a version of C-SCAN
- Arm only goes as far as the last request in each direction, then reverses direction immediately, without first going all the way to the end of the disk
- Total number of cylinders?



# C-LOOK (Cont.)

queue = 98, 183, 37, 122, 14, 124, 65, 67  
head starts at 53





# Selecting a Disk-Scheduling Algorithm



- SSTF is common and has a natural appeal
- SCAN and C-SCAN perform better for systems that place a heavy load on the disk
  - Less starvation
- Performance depends on the number and types of requests
- Requests for disk service can be influenced by the file-allocation method
  - And metadata layout
- The disk-scheduling algorithm should be written as a separate module of the operating system, allowing it to be replaced with a different algorithm if necessary
- Either SSTF or LOOK is a reasonable choice for the default algorithm
- What about rotational latency?
  - Difficult for OS to calculate



# Disk Management



- **Low-level formatting**, or **physical formatting** — Dividing a disk into sectors that the disk controller can read and write
  - Each sector can hold header information, plus data, plus error correction code (**ECC**)
  - Usually 512 bytes of data but can be selectable
- To use a disk to hold files, the operating system still needs to record its own data structures on the disk
  - **Partition** the disk into one or more groups of cylinders, each treated as a logical disk
  - **Logical formatting** or “making a file system”
  - To increase efficiency most file systems group blocks into **clusters**
    - Disk I/O done in blocks
    - File I/O done in clusters




# Disk Management (Cont.)



- Raw disk access for apps that want to do their own block management, keep OS out of the way (databases for example)
- Boot block initializes system
  - The bootstrap is stored in ROM
  - **Bootstrap loader** program stored in boot blocks of boot partition
- Methods such as **sector sparing** used to handle bad blocks



# Booting from a Disk in Windows





# Swap-Space Management




- Swap-space — Virtual memory uses disk space as an extension of main memory
  - Less common now due to memory capacity increases
- Swap-space can be carved out of the normal file system, or, more commonly, it can be in a separate disk partition (raw)
- Swap-space management
  - 4.3BSD allocates swap space when process starts; holds text segment (the program) and data segment
  - Kernel uses **swap maps** to track swap-space use
  - Solaris 2 allocates swap space only when a dirty page is forced out of physical memory, not when the virtual memory page is first created
    - File data written to swap space until write to file system requested
    - Other dirty pages go to swap space due to no other home
    - Text segment pages thrown out and reread from the file system as needed





# Data Structures for Swapping on Linux Systems





# RAID Structure



- RAID – redundant array of inexpensive disks
  - multiple disk drives provides reliability via **redundancy**
- Increases the **mean time to failure**
- **Mean time to repair** – exposure time when another failure could cause data loss
- **Mean time to data loss** based on above factors
- If mirrored disks fail independently, consider disk with 1300,000 mean time to failure and 10 hour mean time to repair
  - Mean time to data loss is  $100,000^2 / (2 * 10) = 500 * 10^6$  hours, or 57,000 years!
- Frequently combined with **NVRAM** to improve write performance
- Several improvements in disk-use techniques involve the use of multiple disks working cooperatively



# RAID (Cont.)



- Disk **striping** uses a group of disks as one storage unit
- RAID is arranged into six different levels
- RAID schemes improve performance and improve the reliability of the storage system by storing redundant data
  - **Mirroring** or **shadowing (RAID 1)** keeps duplicate of each disk
  - Striped mirrors (**RAID 1+0**) or mirrored stripes (**RAID 0+1**) provides high performance and high reliability
  - **Block interleaved parity (RAID 4, 5, 6)** uses much less redundancy
- RAID within a storage array can still fail if the array fails, so automatic **replication** of the data between arrays is common
- Frequently, a small number of **hot-spare** disks are left unallocated, automatically replacing a failed disk and having data rebuilt onto them



# RAID Levels



(a) RAID 0: non-redundant striping.




(b) RAID 1: mirrored disks.



(c) RAID 2: memory-style error-correcting codes.



(d) RAID 3: bit-interleaved parity.



(e) RAID 4: block-interleaved parity.




(f) RAID 5: block-interleaved distributed parity.




(g) RAID 6: P + Q redundancy.



# RAID (0 + 1) and (1 + 0)



a) RAID 0 + 1 with a single disk failure.



b) RAID 1 + 0 with a single disk failure.