



SNS COLLEGE OF TECHNOLOGY (AN AUTONOMOUS INSTITUTION) COIMBATORE-35

II YEAR / III SEMESTER

19CET201-ENGINEERING GEOLOGY





IRON ORE

Iron ores are rocks and minerals from which metallic iron can be economically extracted. The ores are usually rich in iron oxides and vary in color from dark grey, bright yellow, or deep purple to rusty red. The iron is usually found in the form of magnetite (Fe3O4, 72.4% Fe), hematite (Fe2O3, 69.9% Fe), goethite (FeO(OH), 62.9% Fe), limonite (FeO(OH)·n(H2O), 55% Fe) or siderite (FeCO3, 48.2% Fe).







IRON ORE

https://youtu.be/BDzbkJ-hBe4

https://youtu.be/KWa fpaPZMo

https://youtu.be/mmkvILW2z2s





MAGNETITE

Magnetite is magnetic, and hence easily separated from the gangue minerals and capable of producing a high-grade concentrate with very low levels of impurities.

The grain size of the magnetite and its degree of commingling with the silica groundmass determine the grind size to which the rock must be comminuted to enable efficient magnetic separation to provide a high purity magnetite concentrate. This determines the energy inputs required to run a milling operation.

Mining of banded iron formations involves coarse crushing and screening, followed by rough crushing and fine grinding to comminute the ore to the point where the crystallized magnetite and quartz are fine enough that the quartz is left behind when the resultant powder is passed under a magnetic separator.

Generally most magnetite banded iron formation deposits must be ground to between 32 and 45 micrometers in order to produce a low-silica magnetite concentrate. Magnetite concentrate grades are generally in excess of 70% iron by weight and usually are low phosphorus, low aluminium, low titanium and low silica and demand a premium price.





GANGUE MINERALS



ENGINEERING GEOLOGY / 19CET201-EG CIVIL / SNSCT







Due to the high density of hematite relative to associated silicate gangue, hematite beneficiation usually involves a combination of beneficiation techniques.

One method relies on passing the finely crushed ore over a slurry containing magnetite or other agent such as ferrosilicon which increases its density. When the density of the slurry is properly calibrated, the hematite will sink and the silicate mineral fragments will float and can be removed.









- ☐ It is one of the finest iron ores in the world and one of the most important pigment minerals as well.
- □ It is a dense and inexpensive material.
- □ It is also used for ballasts for ships.
- □ It is used as gemstones or in making jewellery as well.
- □ It can be used for its calming and protective properties.
- □ It is used as polishing compounds.
- □ Hematite is also kept in the homes because it gives great energy and the ability to get the mind to focus.





Mohs Scale of Mineral Hardness







Mohs relative hardness	Mineral example	Scratch test
1	Talc	Scratch with fingernail
2	Gypsum	Scratch with fingernail
3	Calcite	Scratch with copper penny
4	Fluorite	Easily scratch with knife
5	Apatite	Scratch with knife blade
6	Orthoclase	Scratch with steel file
7	Quartz	Scratch with window glass
8	Topaz	Scratches quartz
9	Corundum	Scratches topaz
10	Diamond	Scratches corundum





THANK YOU...

11/29/23

ENGINEERING GEOLOGY / 19CET201-EG CIVIL / SNSCT