



IoT Platforms Design Methodology

- Purpose & Requirements Specification
- Process Specification • Domain Model Specification
- Information Model Specification
- Service Specifications
- IoT Level Specification
- Functional View Specification
- Operational View Specification
- Device & Component Integration
- Application Development

PURPOSE & REQUIREMENTS SPECIFICATION

The first step in IoT system design methodology is to define the purpose and requirements of the system. In this step, the system purpose, behavior and requirements (such as data collection requirements, data analysis requirements, system management requirements, data privacy and security requirements, user interface requirements, ...) are captured. • Applying this to our example of a smart home automation system, the purpose and requirements for the system may be described as follows: • Purpose : A home automation system that allows controlling of the lights in a home remotely using a web application. • Behavior : The home automation system should have auto and manual modes. In auto mode, the system measures the light level in the room and switches on the light when it gets dark. In manual mode, the system provides the option of manually and remotely switching on/off the light. • System Management Requirement : The system should provide remote monitoring and control functions. • Data Analysis Requirement : The system should perform local analysis of the data. • Application Deployment Requirement : The application should be deployed locally on the device, but should be accessible remotely. • Security Requirement : The system should have basic user authentication capability.

PROCESS SPECIFICATION

The second step in the IoT design methodology is to define the process specification. In this step, the usecases of the IoT system are formally described based on and derived from the purpose and requirement specifications. Define the process with the help of use cases • The use cases are formally described based on Purpose & requirement specification In this From the process specification and information model we identify the states and attributes. For each state and attributes we define a service. These services either change a state or attribute values and are retrieve the current values. For example, the mode service sets mode to auto or manual or retrieves the current mode. The state services sets the light appliances state to ON or OFF. In the auto mode, the controller service monitors the light level in auto mode and switches the light ON or OFF and updates the status in the status database. In manual mode the controller service retrieves the current state from the database and switches the light ON or OFF. The figure deriving services from process specification and information model for home automation IoT system.



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING
DOMAIN MODEL SPECIFICATION

Describes the main concepts, entities and objects in the • The third step in the IoT design methodology is to define the Domain Model. The domain model describes the main concepts, entities and objects in the domain of IoT system to be designed. Domain model defines the attributes of the objects and relationships between objects. Domain model provides an abstract representation of the concepts, objects and entities in the IoT domain, independent of any specific technology or platform. With the domain model, the IoT system designers can get an understanding of the IoT domain for which the system is to be designed. of IoT system to be designed • It defines the attributes of the objects and relationships between them • Entities , Objects and Concepts include the following : Physical entity, Virtual entity , Device, Resource, Service • Physical Entity: – Discreet identifiable entity in physical environment– For eg. Pump, motor, LCD – The IoT System provides the information about the physical entity (using sensors) or performs actuation upon the Physical entity(like switching a motor on etc.) – In smart irrigation example, there are three Physical entities involved : • Soil (whose moisture content is to be monitored) • Motor (to be controlled) • Pump (To be controlled) • Virtual Entity: – Representation of physical entity in digital world – For each physical entity there is a virtual entity • Device: – Medium for interactions between Physical and Virtual Entities. – Devices (Sensors) are used to gather information from the physical entities – Devices are used to identify Physical entities (Using Tags) – In Smart Irrigation System, device is soil moisture sensor and buzzer as well as the actuator (relay switch) attached to it. In smart irrigation system there are three services : – A service that sets the signal to low/ high depending upon the threshold value – A service that sets the motor state on/off – A controller service that runs and monitors the threshold value of the moisture and switches the state of motor on/off depending upon it. When threshold value is not crossed the controller retrieves the motor status from database and switches the motor on/off.

INFORMATION MODEL SPECIFICATION

The fourth step in the IoT design methodology is to define the Information Model. Information Model defines the structure of all the information in the IoT system, for example, attributes of Virtual Entities, relations, etc. Information model does not describe the specifics of how the information is represented or stored. To define the information model, we first list the Virtual Entities defined in the Domain Model. Information model adds more details to the Virtual Entities by defining their attributes and relations. Defines the structure of all the information in the IoT system (such as attributes, relations etc.) • It does not describe the specifics of how the information is represented or stored. • This adds more information to the Virtual entities by defining their attributes and relations • I: e, Draw Class diagram

SERVICE SPECIFICATIONS

The fifth step in the IoT design methodology is to define the service specifications. Service specifications define the services in the IoT system, service types, service inputs/output, service endpoints, service schedules, service preconditions and service effects. The following figures shows deriving the services from the process specification and information model for the home automation IoT system. Define the services in IoT System, service types, service inputs/outputs, service endpoints, service schedules, service preconditions and service effects • Services can be controller service, Threshold service, state service for smart irrigation system • These services either change the state/attribute values or retrieve the current vlues. • For eg. – Threshold service sets signal to high or low depending upon the soil moisture value. – State service sets the motor state : on or off – Controller service monitors the threshold value as well as the motor state and switches the motor on/off and



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

updates the status in the database
Controller Service: In the auto mode, the controller service monitors the light level in auto mode and switches the light ON or OFF and updates the status in the status database. In manual mode the controller service retrieves the current state from the database and switches the light ON or OFF
Mode Service: Sets mode to auto or manual or retrieves the current mode
State Service : Sets the light appliances state to ON or OFF. State Service: Sets the light appliances state to ON or OFF.

IOT LEVEL SPECIFICATION

The sixth step in the IoT design methodology is to define the IoT level for the system. There are 6 IoT deployment levels. The following diagram shows deployment level of the home automation system of Level 1.

Functional View Specifications

The seventh step in the IoT design methodology is to define the Functional View. The Functional View (FV) defines the functions of the IoT systems grouped into various Functional Groups (FGs). Each Functional Group either provides functionalities for interacting with instances of concepts defined in the Domain Model or provides information related to these concepts. The Functional Groups (FG) included in a Functional View include:
Device: the device FG contains devices for monitoring and control. In the home automation example, the device FG includes a single board minicomputer, a light sensor and relay switch (actuator)
Communication : The communication FG handles the communication for the IoT system. The communication FG includes the communication protocols that form the backbone of IoT systems and enable network connectivity. The communication API home automation example is a REST based APIs.
Services : The service FG includes various services involved in the IoT system such as services for device monitoring , device control services , data publishing services and services for device discovery. In home automation example, there are two REST services (mode and state) and one native service (controller service).
Management: the management FG includes all functionalities that are needed to configure and manage IoT System.
Security: the security FG includes security mechanisms for the IoT system such as authentication, authorization , data security etc.,
Application :the application FG includes applications that provide an interface to the users to control and monitor various aspects of the IoT system. Applications also allow users to view the system status and the processed data.

OPERATIONAL VIEW SPECIFICATIONS

The eighth step in the IoT design methodology is to define the Operational View Specifications. In this step, various options pertaining to the IoT system deployment and operation are defined, such as, service hosting options, storage options, device options, application hosting options, etc The following figure shows an example of mapping functional groups to operational view specifications for IoT home automation system. Operational view specifications for the home automation example are as follows.
Devices: Computing Device , Raspberry PI, Light dependent resistor (sensor), relay switch (actuator)
Communication APIs REST APIs
Communication Protocols: Link Layer-802.11, Network Layer- IPv4/IPv6, Transport Layer –TCP, Application Layer- HTTP
Services: i)Controller Service- Hosted on device, Implemented Python and run as a native service. ii)Mode Service-REST-ful web service, hosted on device, implemented with Django – REST frame work. iii) State Service- RESTful REST-ful web service, hosted on device, implemented with Django – REST frame work.
Application: i) Web Application- Django web application , ii)Application Server- Django App server iii) Database Server- MySQL
Security: i) Authentication- Web App, Database ii) Authorization- Web App, Database



SNS COLLEGE OF TECHNOLOGY, COIMBATORE –35 (An Autonomous Institution)



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

Management: 18PCSC41-Internet of Things 2020-2021(EVEN) 13 M.Sc(CS) CS Department- MTNC

i) Application Management-Django App Management ii) Database Management- My SQL, DB Management iii) Device Management- Raspberry Pi Device Management.

DEVICE & COMPONENT INTEGRATION

The ninth step in the IoT design methodology is the integration of the devices and components. The following figure shows the schematic diagram of the IoT Home automation System. The devices and component used in this example are Raspberry Pi mini computer, LDR sensor and relay switch actuators.

APPLICATION DEVELOPMENT

The final step in the IoT design methodology is to develop the IoT application. The following figure shows the screenshot of the home automation web application. The application has controls for the mode (auto ON or auto OFF) and the light ON or OFF. In the auto mode, the IoT system controls the light appliance automatically based on the lighting conditions in the room. When auto mode is enable, the light control in the application is disabled and reflects the current state of the light. When the auto mode is disabled, the light control is enabled and is used for manually controlling the light. • Auto • Controls the light appliance automatically based on the lighting conditions in the room Light • When Auto mode is off, it is used for manually controlling the light appliance. • When Auto mode is on, it reflects the current state of the light appliance.